Safety Data Sheet: EZ GLIDE

Supercedes Date 03/23/2011 Issuing Date 12/23/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name EZ GLIDE
Recommended use Cutting
Information on Manufacturer
Trust-X by Partsmaster, Div of NCH Corp.

P.O. Box 655326 Dallas, TX 75265-5326 Product Code 87600435 Chemical nature mixture Emergency Telephone Number CHEMTREC® 800-424-9300

Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Color Black Physical State Solid Odor Odorless

GHS

Classification

Physical Hazards

None

Health Hazard

Acute Oral Toxicity

Category 5
Serious Eye Damage/Eye Irritation

Category 2B

Other hazards

None

Labeling

Signal Word

WARNING

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after

nandling

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists, get medical attention.

 $\ensuremath{\mathsf{P340}}$ - IF INHALED: Remove person to fresh air and keep at rest

in a position comfortable for breathing.

P342 + P311 - If experiencing respiratory symptoms, call a physician

43 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS						
Component CAS-No Weight %						
Aluminum oxide	1344-28-1	60-100				
Phenyl Formaldehyde	9003-35-4	15-30				
Potassium aluminu, cryolite	60304-36-1	7-13				
Fiberglass	65997-17-3	7-13				

4. FIRST AID MEASURES

General advice Avoid breathing dust. Avoid contact with skin, eyes and clothing.

Eye Contact Do not rub your eyes . Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation

persists, consult a specialist.

Skin Contact Wash affected areas with plenty of soap and water for several minutes. Seek medical attention if

irritation develops.

Inhalation Have the person blow their nose to remove the substance from nasal passages and keep from

inhaling further. Get medical attention if symptoms occur.

Ingestion Clean mouth with water and afterwards drink plenty of water. Get medical attention if symptoms

occur.

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

87600435 - EZ GLIDE Issuing Date 12/23/2013

Flash Point The product is not flammable Method Not applicable

Upper No data available Lower No data available

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Dust can form an explosive mixture in air.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

 NFPA
 Health 1
 Flammability 0
 Instability 0

 HMIS
 Health 1
 Flammability 0
 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsEnsure adequate ventilation. Avoid breathing dust.Environmental PrecautionsNo special environmental precautions required.Methods for ContainmentPick up and arrange disposal without creating dust.

Methods for Cleaning Up Avoid dust formation. Sweep up or vacuum up spillage and collect in suitable container for disposal.

Pick up product and inspect for torn or damage areas . Do not use if product is torn or damage .

Neutralizing Agent Not applicable.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation. Comply with RPM rating on each product . Avoid breathing dust. Avoid

contact with skin, eyes and clothing. Handle and store in accordance with ANSI Standard B7.1.

Storage Keep in a dry place.

Storage Temperature Minimum No information available Maximum No information available

Storage Conditions Indoor X Outdoor Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Aluminum oxide	TWA: 1 mg/m ³	TWA: 15 mg/m ³	No data available
		TWA: 5 mg/m ³	
Phenyl Formaldehyde	No data available	No data available	No data available
Potassium aluminu, cryolite	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	No data available
Fiberglass	TWA: 1 fiber/cm3	No data available	No data available
	TWA: 5 mg/m ³		

Engineering Measures Personal Protective Equipment

Provide appropriate exhaust ventilation at places where dust is formed.

Eye/Face Protection

Tightly fitting safety goggles.

Skin Protection Leather gloves Respiratory Protection Wear a MSHA/I

Wear a MSHA/NIOSH approved respirator if exposure limits are exceeded or where dust exposure

are excessive.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Hearing protection may be required for grinding operations . As needed

hearing protection, OSHA 29CFR 1910.95.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical StateSolidViscosityNot applicableColorBlackOdorOdorless

Odor ThresholdNot applicableAppearanceTextured black pastepHNot applicableSpecific GravityNo information availableEvaporation RateNot applicablePercent Volatile (Volume)No information available

VOC Content (%) Not applicable Vapor Pressure Not applicable Not applicable Vapor Density Solubility Insoluble Melting Point/Range n-Octanol/Water Partition No data available No data available **Decomposition Temperature** No data available **Boiling Point/Range** Not applicable

Flammability (solid, gas) No data available

Flash Point The product is not flammable Method Not applicable

Autoignition Temperature No information available.

Upper No data available Lower No data available

10. STABILITY AND REACTIVITY

Chemical Stability
Conditions to Avoid
Incompatible Products

Hazardous Decomposition Products Possibility of Hazardous Reactions

Stable under normal conditions.

Keep away from open flames, hot surfaces, and sources of ignition

Strong oxidizing agents, Acids.

Traces of, traces of fluorinated products, Formaldehyde.

None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50 No information available
Dermal LD50 No information available

Inhalation LC50

Gas No information available
Mist No information available
Vapor No information available

Principle Route of Exposure

Primary Routes of Entry Acute Effects Inhalation Inhalation

ffects

Eyes Dust may cause abrasive injury to the eye seen as stinging, tearing, redness, or scratching of the

cornea.

Skin Excessive contact may cause mechanical irritation seen as itching and redness .

Inhalation The dust generated during the use of this product is classified by OSHA as inert dust or nuisance

dust and has the same pulmonary effects of inert dust with symptoms that may include soreness of the nose and throat, coughing and sneezing . Prolonged exposure to grinding dust may cause upper

respiratory problems or aggravate existing conditions .

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity

Long term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of

coughing, shortness of breath and diminishing breath capacity. Most of the dust generated during the sanding is from the base material being worked and the potential hazard from this exposure must be evaluated . Repeated contact may cause allergic reactions in very susceptible persons. For products containing Phenol and Formaldehyde which under excessive exposure may cause skin sensitization and airway obstruction . Excessive exposure to inorganic fluorides have shown to

cause excessive calcification of the bones.

Target Organ Effects
Aggravated Medical Conditions

Respiratory system Respiratory disorders

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Aluminum oxide	> 5000 mg/kg (Rat)	no data available	no data available	no data available	no data available
Phenyl Formaldehyde	no data available	no data available	no data available	no data available	no data available
Potassium aluminu, cryolite	= 2150 mg/kg (Rat)	no data available	no data available	no data available	no data available
Fiberglass	no data available	no data available	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Aluminum oxide	no data available	no data available	no data available	no data available	eyes,respiratory
					system,skin
Phenyl Formaldehyde	no data available	no data available	no data available	no data available	no data available
Potassium aluminu, cryolite	no data available	no data available	no data available	no data available	no data available
Fiberglass	no data available	no data available	no data available	no data available	no data available

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
Aluminum oxide	not applicable				
Phenyl Formaldehyde	not applicable				
Potassium aluminu, cryolite	not applicable				
Fiberglass	not applicable				

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

	Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Aluminum oxide no data available	Aluminum oxide	no data available	no data available	no data available	no data available	N/A

Phenyl Formaldehyde	no data available	no data available	no data available	no data available	N/A
Potassium aluminu, cryolite	no data available	no data available	no data available	no data available	N/A
Fiberglass	no data available	no data available	no data available	no data available	N/A

Persistence and DegradabilityNo information available.BioaccumulationNo information available.MobilityNo information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.

Container Disposal Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Aluminum oxide	1344-28-1	60-100	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of	Reactive Hazard
			Pressure Hazard	
Yes	Yes	No	No	No
CERCI A				

Component	Hazardous Substances RQs	CERCLA EHS RQs
Aluminum oxide	Not applicable	Not applicable
Phenyl Formaldehyde	Not applicable	Not applicable
Potassium aluminu, cryolite	Not applicable	Not applicable
Fiberglass	Not applicable	Not applicable

16. OTHER INFORMATION

Prepared ByDon StewartSupercedes Date03/23/2011Issuing Date12/23/2013

Reason for RevisionNo information available.GlossaryNo information available.List of References.No information available.

Trust-X by Partsmaster, Div of NCH Corp.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.