

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Goof Off Professional Strength VOC Compliant	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact Information:	3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
Product Category:	General Purpose Adhesive Remover	
Intended Use:	Mult-Purpose Remover for tar, ink, paint, adhesive, etc.	
Synonyms:	FG603, FG603BULK, FG612, FG650, FG650SK, FG650LWS, FG650LDS, FG651, FG651BULK, FG651BULK2, FG651BULK3, FG653, FG653B, FG653BBLK, FG654, FG654BWS, FG654LWS, FG655B, FG655BUL, FG655BWS, FG657, FG683, FG690, FG750, 2410B.3	
Additional Information	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Carcinogenicity, Category 2
Specific Target Organ Toxicity (single exposure), Category 3
Aspiration Toxicity, Category 1



GHS Signal Word:	Danger
GHS Hazard Phrases:	H225: Highly flammable liquid and vapor. H315: Causes skin irritation. H319: Causes serious eye irritation. H351: Suspected of causing cancer. H335: May cause respiratory irritation. H304: May be fatal if swallowed and enters airways.
GHS Precaution Phrases:	P233: Keep container tightly closed. P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting equipment. P243: Take precautionary measures against static discharge. P242: Use only non-sparking tools. P264: Wash hands thoroughly after handling. P362+364: Take off contaminated clothing and wash it before reuse. P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood.

GHS Response Phrases:


P281: Use personal protective equipment as required.
 P261: Avoid breathing gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.
 P370+378: In case of fire, use dry chemical powder to extinguish.
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P302+352: IF ON SKIN: Wash with plenty of soap and water.
 P321: Specific treatment see instructions on label.
 P332+313: If skin irritation occurs, get medical advice/attention.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+313: If eye irritation persists, get medical advice/attention.
 P308+313: IF exposed or concerned: Get medical attention/advice.
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312: Call a POISON CENTER/doctor if you feel unwell.
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P331: Do NOT induce vomiting.

GHS Storage and Disposal Phrases:

P403+235: Store in cool/well-ventilated place.
 P501: Dispose of contents/container according to local, state and federal regulations.
 P405: Store locked up.
 P403+233: Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous atmosphere.

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL		0
PPE		X

**HMIS:****OSHA Regulatory Status:**

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

This product has not been tested as a whole to determine health effects. The health effects listed below are associated with the individual ingredients listed in Section 3.

INHALATION:

High vapor concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, loss of consciousness and even death). Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

EYES:

High vapor concentrations may cause irritation of the eyes. Causes eye irritation.

SKIN:

Prolonged or repeated contact may cause drying, cracking, or irritation.

INGESTION:

Harmful or fatal if swallowed. Pulmonary aspiration hazard. Ingestion may cause nausea, vomiting, diarrhea and inflammation of the lungs. Irritating to the throat, mouth, and stomach. May produce central nervous system effects, which include dizziness, loss of balance and coordination, unconsciousness, coma and even death.

CHRONIC OVEREXPOSURE EFFECTS:

Goof Off Professional Strength VOC Compliant

Printed: 04/15/2015

Revision: 04/15/2015

Supersedes Revision: 03/03/2015

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal. Overexposure may cause liver and kidney injury.

TARGET ORGANS: liver, kidneys, central nervous system

PRIMARY ROUTES OF ENTRY: inhalation, ingestion, absorption

Medical Conditions Generally Aggravated By Exposure: The following diseases or disorders may be aggravated by exposure to this product: skin, eye, liver, kidney, nervous system, respiratory system

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
67-64-1	Acetone {2-Propanone}	60.0 -100.0 %	AL3150000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	<18.0 %	ZE2100000
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	< 5.5 %	DA0700000
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	< 0.2 %	GR8575000

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration.

Signs and Symptoms Of Exposure:

See Potential Health Effects.

Note to Physician:

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE FIGHTING MEASURES

Flammability Classification:	NFPA Class IB
Flash Pt:	-4.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Carbon dioxide, dry chemical, foam and/or water fog.
Unsuitable Extinguishing Media:	None known.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, sparks, flame, and other ignition sources distant from material handling point.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	<p>Vapors may cause flash fire or ignite explosively.</p> <p>Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.</p> <p>Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.</p> <p>Large spills: Dike far ahead of spill for later disposal.</p> <p>Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.</p>
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	<p>Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.</p> <p>Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.</p> <p>Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.</p> <p>Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.</p>
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

Other Precautions: Keep away from heat, sparks and open flame. No smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	PEL: 50 ppm	TLV: 50 ppm	No data.

Respiratory Equipment (Specify Type): If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Eye Protection: Chemical goggles, also wear a face shield if a splashing hazard exists.

Protective Gloves: Appropriate chemical resistant gloves should be worn, such as nitrile rubber. Wear gloves with as much resistance to the chemical ingredients as possible. Other glove materials may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing: To prevent skin contact wear protective clothing covering all exposed areas.

Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.

Engineering Controls (Ventilation etc.): Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

Work/Hygienic/Maintenance Practices: Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.

Do not eat, drink, or smoke in the work area.

Discard any clothing or other protective equipment that cannot be decontaminated.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid
Appearance and Odor: Water white, free and clear.
Melting Point: No data.
Boiling Point: 150.00 F
Autoignition Pt: No data.
Flash Pt: -4.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits: LEL: No data. UEL: No data.
Specific Gravity (Water = 1): 0.797 - 0.8021
Density: 6.65 LB/GL
Vapor Pressure (vs. Air or mm Hg): No data.
Vapor Density (vs. Air = 1): > 1
Evaporation Rate: > 1
Solubility in Water: Slight
Viscosity: < 5 cps
Percent Volatile: 100.0 % by weight.
VOC / Volume: 20.0000 % WT
Additional Physical Information VOC (g/L): 161 g/L max

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]
Conditions To Avoid - Instability: No data available.
Incompatibility - Materials To Avoid: Strong oxidizing agents.
Hazardous Decomposition Or Byproducts: Carbon monoxide, carbon dioxide.
Possibility of Hazardous Reactions: Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions: No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information:	This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.
Chronic Toxicological Effects:	<p>CAS# 67-64-1: Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe. Result: Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning. - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946</p> <p>CAS# 1330-20-7: Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H. Result: Behavioral: Muscle contraction or spasticity. Lungs, Thorax, or Respiration: Other changes. - Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe. Result: Behavioral: General anesthetic. Behavioral: Somnolence (general depressed activity). Behavioral: Irritability. - "Sbornik Vysledku Toxilogickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972</p> <p>CAS# 100-41-4: Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm. Result: Tumorigenic: Carcinogenic by RTECS criteria. Kidney, Ureter, Bladder: Tumors.</p> <p>Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe. Result: Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants). Effects on Fertility: Litter size (e.g.: # fetuses per litter; measured before birth). Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946</p>
Carcinogenicity/Other Information:	ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans ACGIH A4 - Not Classifiable as a Human Carcinogen IARC 2B - Possibly Carcinogenic to Humans IARC 3: Not Classifiable as to Carcinogenicity in Humans.

SAFETY DATA SHEET

Goof Off Professional Strength VOC Compliant

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	n.a.	2B	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: This product has not been tested as a whole. Information below will be for individual ingredients.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste at an approved hazardous waste treatment/disposal facility in accordance with applicable local, provincial and federal regulations.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263 **Packing Group:** II



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Paint Related Material

Additional Transport Information: The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes 100 LB	Yes
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes 1000 LB	Yes
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	No	Yes 5000 LB	Yes

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Fire Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Sudden Release of Pressure Hazard

SAFETY DATA SHEET

Goof Off Professional Strength VOC Compliant

Page: 9
Printed: 04/15/2015
Revision: 04/15/2015
Supersedes Revision: 03/03/2015

[] Yes [X] No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: Yes

Regulatory Information:

16. OTHER INFORMATION

Revision Date: 04/15/2015
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.