

MATERIAL SAFETY DATA SHEET

Klean-Strip Acetone

Page: 1

| | | |
|---------------|--|---|
| HEALTH | | 1 |
| FLAMMABILITY | | 3 |
| PHYSICAL HAZ. | | 0 |
| PPE | | |



Printed: 12/30/2008
Revision: 11/13/2008
Supersedes Revision: 03/13/2006
Date Created: 05/18/2005

1. Product and Company Identification

Product Code: 1640.1
Product Name: Klean-Strip Acetone
Reference #: 1640.1
Manufacturer Information
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Web site address: www.wmbarr.com
Preparer Name: W.M. Barr EHS Department (901)775-0100
Synonyms

CAC18, DAC18, GAC18, GAC718, QAC18, QAC18L, QAC718, QAC18L

2. Composition/Information on Ingredients

| Hazardous Components (Chemical Name) | CAS # | Concentration | OSHA PEL | ACGIH TWA | ACGIH STEL |
|--------------------------------------|---------|---------------|----------|-----------|------------|
| 1. Acetone | 67-64-1 | 100.0 % | 1000 ppm | 500 ppm | 750 ppm |

3. Hazards Identification

Emergency Overview

Danger! Extremely Flammable. Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from the work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling, or building during use and until all vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic)

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness, headache, watering of eyes, irritation of respiratory tract, drowsiness, nausea, and numbness in fingers, arms and legs.

Skin Contact Acute Exposure Effects:

May cause drying of skin, and numbness in fingers and arms. Liquid is absorbed readily.

Eye Contact Acute Exposure Effects:

This material is an eye irritant.

Ingestion Acute Exposure Effects:

Harmful if swallowed. May cause dizziness, headache, nausea, and irritation of the mouth, throat, and stomach.

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other

MATERIAL SAFETY DATA SHEET

Klean-Strip Acetone

Page: 2

Printed: 12/30/2008

Revision: 11/13/2008

Supersedes Revision: 03/13/2006

physiological damage. May cause weakness, fatigue, skin irritation, and numbness in hands and feet.

Signs and Symptoms Of Exposure

Primary Routes of Exposure:

Inhalation, ingestion, and dermal.

Medical Conditions Generally Aggravated By Exposure

Skin, eye, lung (asthma-like conditions)

4. First Aid Measures

Emergency and First Aid Procedures

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be reached.

Skin Contact:

Wash with soap and water.

Eye Contact:

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:

Call your poison control center, hospital emergency room, or physician immediately for instructions.

Note to Physician

Call your local poison control center for further instructions.

5. Fire Fighting Measures

Flammability Classification:

Class IB

Flash Pt:

-4.00 F Method Used: TAG Closed Cup

Explosive Limits:

LEL: 2.5 % at 77.0 F UEL: 13.0 % at 77.0 F

Autoignition Pt:

869.00 F

Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Flammable Properties and Hazards

Extremely Flammable!

Hazardous Combustion Products

carbon monoxide, carbon dioxide

Extinguishing Media

Use carbon dioxide, dry powder, or foam.

Unsuitable Extinguishing Media

No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Clean Up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. For small spills, take up liquid with sand, earth, or other noncombustible absorbent material and place in a container for disposal. For large spills, dike far ahead of spill and use sand, earth, or other noncombustible absorbent material and then place material in a container for disposal.

MATERIAL SAFETY DATA SHEET

Klean-Strip Acetone

Page: 3

Printed: 12/30/2008

Revision: 11/13/2008

Supercedes Revision: 03/13/2006

Waste Disposal:

Dispose in accordance with applicable local, state, and federal regulations.

7. Handling and Storage

Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations.

Do not reuse the container.

Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. Exposure Controls/Personal Protection

Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves

Wear chemical resistant gloves suited for use with acetone. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.)

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or your experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

9. Physical and Chemical Properties

| | |
|---|--|
| Physical States: | [] Gas [X] Liquid [] Solid |
| Melting Point: | No data. |
| Boiling Point: | > 131.00 F |
| Autoignition Pt: | 869.00 F |
| Flash Pt: | -4.00 F Method Used: TAG Closed Cup |
| Explosive Limits: | LEL: 2.5 % at 77.0 F UEL: 13.0 % at 77.0 F |
| Specific Gravity (Water = 1): | 0.789 |
| Density: | 6.572 LB/GA at 77.0 F |
| Vapor Pressure (vs. Air or mm Hg): | 213 MM HG at 77.0 F |

MATERIAL SAFETY DATA SHEET

Klean-Strip Acetone

Page: 4

Printed: 12/30/2008

Revision: 11/13/2008

Supersedes Revision: 03/13/2006

Vapor Density (vs. Air = 1): No data.
Evaporation Rate (vs Butyl Acetate=1): No data.
Solubility in Water: No data.
Percent Volatile: 100.0 % by weight.
Corrosion Rate: No data.
pH: No data.

Appearance and Odor

Clear colorless liquid with a characteristic ketone odor.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

No data available.

Incompatibility - Materials To Avoid

May form explosive mixtures with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers.

Hazardous Decomposition Or Byproducts

Decomposition may produce carbon monoxide, carbon dioxide, and other asphyxiants.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Polymerization

No data available.

11. Toxicological Information

LD50 Rat oral 10.7 mL/kg (=8450 mg/kg bw); acetone given by gastric intubation to groups of five non-fasted Carworth-Wistar female rats
LD50 Rat oral 9800 mg/kg/ bw
LD50 Rat oral 5800 mg/kg bw
LD50 Mouse oral 3000 mg/kg bw
LD50 Rabbit oral 5340 mg/kg bw
LC50 Rat inhalation exposure 76 mg/L/4 hr
LC50 Rat inhalation 50.1 mg/L/8 hr
LD50 Rabbit dermal 20 mg/kg bw
LD50 Rabbit dermal 20,000 mg/kg bw
LD50 Mouse ip 1,297 mg/kg bw
LD50 Rat iv 5500 mg/kg bw
LD50 Mouse oral 5.2 g/kg

Carcinogenicity/Other Information

No data available.

| Hazardous Components (Chemical Name) | CAS # | NTP | IARC | ACGIH | OSHA |
|--------------------------------------|---------|------|------|-------|------|
| 1. Acetone | 67-64-1 | n.a. | n.a. | A4 | n.a. |

12. Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method

Dispose in accordance with applicable local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

Klean-Strip Acetone

Page: 5

Printed: 12/30/2008

Revision: 11/13/2008

Supersedes Revision: 03/13/2006

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name Acetone

DOT Hazard Class: 3
DOT Hazard Label: FLAMMABLE LIQUID
UN/NA Number: UN1090
Packing Group: II

Additional Transport Information

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. Regulatory Information

US EPA SARA Title III

| Hazardous Components (Chemical Name) | CAS # | Sec.302 (EHS) | Sec.304 RQ | Sec.313 (TRI) | Sec.110 |
|--------------------------------------|---------|---------------|-------------|---------------|---------|
| 1. Acetone | 67-64-1 | No | Yes 5000 LB | No | Yes |

SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

Sec.302: EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.

Sec.304: EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.

Sec.313: EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.

Sec.110: EPA SARA 110 Superfund Site Priority Contaminant List

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

Yes No Acute (immediate) Health Hazard
 Yes No Chronic (delayed) Health Hazard
 Yes No Fire Hazard
 Yes No Sudden Release of Pressure Hazard
 Yes No Reactive Hazard

16. Other Information

Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.