

# MATERIAL SAFETY DATA SHEET

2/18/16

## 1. Product and Company Identification

**Material name** STATIC GUARD ANTISTATIC SPRAY  
**Revision date** 03-Mar-2010  
**CAS #** Mixture  
**Product use** ANTI-STATIC SPRAY  
**Company information** ALBERTO-CULVER USA, INC.  
2525 Armitage Avenue  
Melrose Park, IL 60160 US  
Business Phone (708) 450-3000  
Emergency Phone (708) 450-3175  
Shipping Emergencies CHEMTREC 800 424-9300 or 703 527-3887  
**Emergency** Emergency Phone (708) 450-3175  
Shipping Emergencies CHEMTREC 800 424-9300 or 703 527-3887  
**General information** Business Phone (708) 450-3000

Static Guard  
Antistatic spray

## 2. Hazards Identification

**Emergency overview** CONTENTS UNDER PRESSURE.  
EXTREMELY FLAMMABLE. Will be easily ignited by heat, spark or flames.

Contact with eyes may cause irritation.

### Potential short term health effects

**Eyes** Contact with eyes may cause irritation. Health injuries are not known or expected under normal use.

**Skin** Health injuries are not known or expected under normal use.

**Inhalation** Health injuries are not known or expected under normal use. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**Ingestion** Do not ingest. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Health injuries are not known or expected under normal use.

**Target organs** Central nervous system. Eyes. Respiratory system. Skin.

**Chronic effects** Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

**Main symptoms** Conjunctivitis. Rash. Irritation. Defatting of the skin. Narcosis. Behavioral changes. Decrease in motor functions.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
ALCOHOL DENAT.	64-17-5	< 80
Isobutane	75-28-5	< 10
Hydrofluorocarbon 152A	75-37-6	< 20
Propane	74-98-6	< 2.5

**Composition comments** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

## 4. First Aid Measures

### First aid

**Eye contact** Immediately flush eyes with plenty of water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops or persists.

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Ingestion** Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If ingestion of a large amount does occur, seek medical attention.

**Notes to physician** Symptoms may be delayed.

Material name: STATIC GUARD ANTISTATIC SPRAY

Formula: F81222-C1 Version #: 1.0 Revision date: 03-MAR-2010 Print date: 03-MAR-2010

MSDS US

1 / 5

**General advice**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a physician if symptoms develop or persist. If you feel unwell, seek medical advice (show the label where possible).

**5. Fire Fighting Measures****Unusual fire & explosion hazards**

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard. Containers may explode when heated.

**Suitable extinguishing media**

Small Fires: Dry chemical, CO<sub>2</sub>, water spray or regular foam.

**Fire fighting equipment/instructions**

Large Fires: Water spray, fog or regular foam.

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. ALWAYS stay away from tanks engulfed in flame. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire.

**Special protective equipment for fire-fighters**

Structural firefighters protective clothing will only provide limited protection.

**Specific methods**

In the event of fire and/or explosion do not breathe fumes.

**Flash point**

> -58 °F (> -50 °C) Propellant

**Auto-ignition temperature**

685.4 °F (362.8 °C) estimated

**6. Accidental Release Measures****Containment procedures**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

**Personal precautions**

Ventilate closed spaces before entering. Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep out of low areas. Stay upwind.

**Methods for cleaning up**

Large Spills: Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

**7. Handling and Storage****Handling**

Do not handle or store near an open flame, heat or other sources of ignition. Vapors may form explosive mixtures with air. All equipment used when handling the product must be grounded. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. May be ignited by open flame. Do not breathe gas/fumes/vapor/spray.

**Storage**

Do not handle or store near an open flame, heat or other sources of ignition. Store in cool place. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. The pressure in sealed containers can increase under the influence of heat. Use care in handling/storage. Keep the container dry. Keep this material away from food, drink and animal feed. Keep out of the reach of children.

Level 2 Aerosol

**8. Exposure Controls / Personal Protection****Personal protective equipment****Respiratory protection**

No personal respiratory protective equipment normally required. Applicable for industrial settings only. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Hand protection**

Not normally needed.  
Applicable for industrial settings only. Protective gloves.

**Eye protection**

Avoid contact with eyes.  
Applicable for industrial settings only. Wear chemical goggles.

**Skin and body protection**

Not normally needed. Applicable for industrial settings only. Use personal protective equipment as required.

**Engineering measures to reduce exposure**

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment if high dust/air concentrations are possible. Use explosion-proof ventilation equipment.

**Hygiene measures**

Avoid contact with eyes. When using do not smoke. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.

**9. Physical & Chemical Properties**

Boiling point	> 1.4 °F (> -17.2 °C)
Flammability	Not available.
Form	Aerosol.
Percent volatile	90.6097 % estimated
Vapor pressure	47 - 57 psi At 70°F
VOC	79.506 %

**10. Chemical Stability & Reactivity Information**

Stability	Risk of explosion. Risk of ignition.
Incompatibility	Acids. Amines. Isocyanates. Strong oxidizing agents.

**11. Toxicological Information****Toxicology data for the preparation**

Local effects	Contact may irritate or burn eyes.
Carcinogenicity	
US ACGIH Threshold Limit Values: A4 carcinogen	
ALCOHOL DENAT.	64-17-5 Group A4 Not classifiable as a human carcinogen.
Reproductivity	Possible reproductive hazard.
Chronic toxicity	Prolonged exposure may cause chronic effects.
Further information	Symptoms may be delayed.

**12. Ecological Information**

Ecotoxicity	This material is not expected to be harmful to aquatic life. Components of this product have been identified as having potential environmental concerns.
-------------	--

**Invertebrate Toxicity: EC50 value**

ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 1.58 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 4 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 2 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 10000 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 10000 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) 7.7 - 11.2 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia obtusa) 10100 - 11200 mg/l 48 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia obtusa) 12300 - 13400 mg/l 24 h Static Intoxication
ALCOHOL DENAT.	64-17-5	Water flea (Daphnia magna) > 100 mg/l 6 h Static Intoxication

**Micro-organisms Toxicity: LC50 value**

ALCOHOL DENAT.	64-17-5	Turbellarian, flatworm (Dugesia tigrina) > 100 mg/l 96 h Static Mortality
----------------	---------	---

**13. Disposal Considerations**

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. If discarded, this product is considered a RCRA ignitable waste, D001. Incinerate the material under controlled conditions in an approved incinerator.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

<= 1L (33.8 Fl. Oz)

**Basic shipping requirements:**

Proper shipping name Consumer commodity

Hazard class ORM-D

Subsidiary hazard class None

**Additional information:**

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

ERG number 126

### Department of Transportation (DOT) Requirements

**Basic shipping requirements:**

Proper shipping name Aerosols, flammable

Hazard class 2.1

UN number UN1950

**Additional information:**

Special provisions 153, N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

ERG number 126



### IATA

<= 1L (33.8 Fl. Oz)

**Basic shipping requirements:**


Proper shipping name Consumer commodity

Hazard class 9

Subsidiary hazard class 3

UN number ID8000

Packaging instructions 910



### IATA

**Basic shipping requirements:**

Proper shipping name Aerosols, flammable

Hazard class 2.1

Subsidiary hazard class 6.1

UN number 1950

Packaging instructions Forbidden



### IMDG

**Basic shipping requirements:**

Proper shipping name AEROSOLS, flammable

Hazard class 2.1

Subsidiary hazard class 3

UN number 1950

**Additional information:**

Item 5F

Labels required 2.1

Transport Category 2



## 15. Regulatory Information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
CERCLA/SARA Hazardous Substances - Not applicable.

### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200  
hazardous chemical Yes

### CERCLA (Superfund) reportable quantity

None

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely  
hazardous substance No

Section 311 hazardous  
chemical Yes

Hazard categories  
Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

### HMIS ratings

Health: 1\*  
Flammability: 4  
Physical hazard: 1

### NFPA ratings

Health: 1  
Flammability: 4  
Instability: 1

### International regulations

The product is classified and labelled in accordance with EC directives or respective national laws.

### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (CCS)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Japanese Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Korean Inventory of Chemicals (KICS)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

### State regulations

#### US - New Jersey Community RTK (EHS Survey): Reportable threshold

Hydrofluorocarbon 152A	75-37-6	500 LBS
Isobutane	75-28-5	500 LBS
Propane	74-98-6	500 LBS

#### US - Pennsylvania RTK - Hazardous Substances: Listed substance

ALCOHOL DENAT.	64-17-5	Listed.
Isobutane	75-28-5	Listed.
Propane	74-98-6	Listed.

## 16. Other Information

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Issue date

03-Mar-2010